

Niekamp Tool Company Retrofit Shower Knob Submittal Sheet

Please Complete Sections 1 - 9:

1. Please mark quantity required in the box to the right of your existing valve type:

Bradley	Equa-Flo 478 Generation 1 (Before March 1982)		Moen	Moentrol (Push-Pull)	
	Equa-Flo 478 Generation 2 (March 1982 – July 2004)			Posi-Temp (.375 x Double Flat)	
	Equa-Flo S59-1005		Powers	HydroGuard 410 (Round Escutcheon)	
Monitor 1300 Series		HydroGuard 420 (Oval Escutcheon)			
Monitor 1400 Series		HydroGuard E427			
Monitor 1500 Series		HydroGuard E700			
Delta	Monitor 1700 Series		Speakman	Sentinel Mark II	
			Symmons	Temptrol with C-5 stem (Requires Stem Modification, Must Purchase Jig Tool)	
Kohler	304 Series (Rite-Temp)			Temptrol with TA-10 Stem	
	LVC Thermostatic ShowerMaster		Zurn	Temp-Gard Z7100	
Leonard	PAM II & 4500 Aquatrol				
	Other	List Details in Blank Space			

2. What is the spline count of the broach (area with splines on the end of the stem) ? _____
3. What is the diameter of the broach (to the nearest 1/16" increment) ? _____
4. How far does the tip of the stem project from the wall (to the nearest 1/16" increment) ? _____ (for more than one measurement please list details below or on separate sheet.)
5. Please mark the box to the right of the diameter & pitch of the existing stem center screw:

8-32		10-24		10-32	
------	--	-------	--	-------	--

6. What is the minimum diameter needed for a new bezel to cover any existing holes / marred tile on the wall ? _____" (Be mindful that the bezel is concentric and tapers toward the stem.)
7. Facility Name: _____
8. Signature: _____
9. Signed by: _____
10. Date: _____